



MATERIAL SAFETY DATA SHEET

Sikabond T-55 US

HMIS

HEALTH	*2
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	C

1. Product And Company Identification

Supplier

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Manufacturer

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Issue Date: 08/03/2007

Product Name: Sikabond T-55 US
CAS Number: Not Established
Chemical Family: Filled Reactive PUR polymer
MSDS Number: 4133
Product Code: 0433546

2. Composition/Information On Ingredients

Ingredient Name	CAS Number		Percent Of Total Weight
POLYISOCYANATE PREPOLYMER	Mixture		
XYLENE (MIXED ISOMERS)	1330-20-7	<	4

3. Hazards Identification

Eye Hazards

Causes eye irritation.

Skin Hazards

May cause skin irritation. Prolonged and/or repeated skin contact may cause an allergic reaction/sensitization.

Ingestion Hazards

May be harmful if swallowed.

Inhalation Hazards

May cause respiratory tract irritation. May cause sensitization. Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney, and Central Nervous

MATERIAL SAFETY DATA SHEET

Sikabond T-55 US

3. Hazards Identification - Continued

Inhalation Hazards - Continued

System damage. May cause nose, throat, and lung irritation.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with soap and plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel. If victim is fully conscious, give one or two cups of water or milk to drink.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Consult physician if symptoms persist.

5. Fire Fighting Measures

Flash Point: >142 °F >61 °C

Autoignition Point: N/AV °F

Lower Explosive Limit: N/AV

Upper Explosive Limit: N/AV

Fire And Explosion Hazards

Combustible liquid. During a fire, irritating and/or toxic gases and aerosols from the decomposition/combustion products may be present.

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO₂.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Eliminate all ignition sources. Use appropriate Personal Protective Equipment (PPE). Absorb and/or contain spill with inert materials (e.g. sand, vermiculite) and then place in appropriate container. For large spills, use water spray to disperse vapors. Prevent runoff from entering waterways or sewers.

7. Handling And Storage

Handling And Storage Precautions

Keep out of reach of children. Store in a cool, dry, well ventilated area. Keep containers tightly closed.

Storage Precautions

Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

MATERIAL SAFETY DATA SHEET

Sikabond T-55 US

8. Exposure Controls/Personal Protection

Engineering Controls

Use of a system of local and/or general exhaust is recommended to keep employee below applicable exposure limits. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Eye/Face Protection

Safety glasses with side shields or goggles.

Skin Protection

Chemical-resistant gloves. Lab coat or other work clothing. Launder before reuse.

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Exposure Limits are exceeded, use a properly fitted NIOSH-approved respirator.

Ingredient(s) - Exposure Limits

XYLENE (MIXED ISOMERS)
OSHA TLV-TWA: 100 ppm
ACGIH TLV-TWA: 100 ppm
ACGIH TLV-STEL: 150 ppm

9. Physical And Chemical Properties

Appearance

Paste

Odor

No odor

Chemical Type: Mixture

Physical State: Liquid

Melting Point: N/AV °F

Boiling Point: N/AV °F

Specific Gravity: 1.34 g/cm³

Percent VOCs: 6.2

Vapor Pressure: N/AV

Vapor Density: N/AV

Solubility: Insoluble

VOC Content: 83 g/L

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability)

Open Flame, Heat

Incompatible Materials

Water, Alcohols, Amines

Hazardous Decomposition Products

CO, CO₂, Hydrogen Chloride, Nitrogen Oxides

MATERIAL SAFETY DATA SHEET

Sikabond T-55 US

11. Toxicological Information

No Data Available...

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. Transport Information

Proper Shipping Name

Not Regulated by the US D.O.T.

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard
Chronic Health Hazard

SARA Title III - Section 313 Supplier Notification

This product contains the following toxic chemicals that are subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372.

XYLENE (MIXED ISOMERS) (1330-20-7) <4 %

This information must be included on all MSDSs that are copied and distributed for this material.

Ingredient(s) - U.S. Regulatory Information

XYLENE (MIXED ISOMERS)
SARA Title III - Section 313 Form "R"/TRI Reportable Chemical
SARA - Acute Health Hazard
SARA - Chronic Health Hazard
SARA - Fire Hazard

Ingredient(s) - State Regulations

XYLENE (MIXED ISOMERS)
New Jersey - Workplace Hazard
New Jersey - Environmental Hazard
New Jersey - Special Hazard
Pennsylvania - Workplace Hazard
Pennsylvania - Environmental Hazard
Massachusetts - Hazardous Substance
New York City - Hazardous Substance

16. Other Information

No Data Available...

MATERIAL SAFETY DATA SHEET

Sikabond T-55 US

16. Other Information - Continued

HMIS Rating

Health: *2

Fire: 2

Reactivity: 0

PPE: C

Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

This MSDS Supercedes A Previous MSDS Dated: 09/25/2006

Disclaimer

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000